



Click to Print This Page



Click to Enlarge This Page

CRL Diamond Drill Selection Chart

Feb-02

Drill Type	Diamond Type	Mounting Style	Approximate # of Holes Using a 2" Drill Bit	Fits Drill CRL Machine	Wall Thickness
DCD Series	Electro-Formed Diamond	Straight Shank	1500 - 2000	CRL2, 41, SDM1, PH1, PH2	.020"
HBT Series	Electro-Formed Diamond	Belgian	1500 - 2000	AMZ1, PDM2800	.020"
PD Series	Metal Bond Diamond	Straight Shank	1000 - 1500	CRL2, 41, SDM1, PH1, PH2	.045"
PDT Series	Metal Bond Diamond	Belgian	1000 - 1500	AMZ1, PDM2800	.045"
EDD Series	Diamond Plated	Straight Shank	150 - 200	CRL2, 41, SDM1, PH1, PH2	.050"
AG Series	Diamond Plated	Straight Shank	150 - 200	CRL2, 41, SDM1, PH1, PH2	.050"
DR Series	Diamond Plated	Straight Shank	125	CRL2, 41, SDM1, PH1, PH2	.050"
REC Series	Diamond Plated	Straight Shank	125	CRL2, 41, SDM1, PH1, PH2	.050"
SRDD Series	Diamond Plated	Straight Shank	50	CRL2, 41, SDM1, PH1, PH2	.040"

Click on a Drill Series or Drill Machine to go to that page.

All information is deemed to be accurate and current to the best of our knowledge. Information based on proper drilling technique and handling of the drill and bit. Remember, proper coolant should always be used when drilling with diamond drills. If up to date information is needed please contact CRL Technical Sales by calling Toll Free (800) 421-6144 extension 777 or by e-mail.