



Click to Print This Page



Click to Enlarge This Page

## SINGLE-COMPONENT ORGANIC SEALANT COMPARISON CHART

February 2002

SINGLE-COMPONENT	CRL	ADCO	BOSTIK	DAP	OSI	PTI	PECORA	PRC/PSI	SCHNEE MOOREHEAD	SIKA	SOMACA	SONNEBORN	TREMCO/MAMECO/VULKEM
<b>POLYURETHANE</b> <b>Federal Specification</b> TT-S-230C, Type 2, Class A ASTM C 920 Type S, Grade NS Class 25	<b>M66</b> (Textured)		Chem-Calk 900 (Smooth)	Polyurethane Adhesive Sealant (Smooth) Polyurethane Concrete Sealant (Textured)	PR-255 (Smooth)		Dynatrol 1-XL (Smooth)	PSI-901 (Smooth)	7100 (Smooth)	1A (Smooth)	One-Part Polyurethane (Grainy and Smooth)	Sonolastic NP1 (Smooth)	Vulkem 116 (Textured) Vulkem 911 Vulkem 931 Tremco Dymonic (Smooth)
<b>POLYURETHANE</b> (LOW MODULUS) <b>Federal Specification</b> TT-S-230C, Type 2, Class A ASTM C 920 Type S, Grade NS Class 25	<b>M64</b> (Smooth)									15LM (Smooth)		Sonolastic 150 (Smooth)	Vulkem 921 (Smooth)
<b>POLYURETHANE</b> (SELF-LEVELING) <b>Federal Specification</b> TT-S-230C, Type 1, Class A ASTM C 920 Type S, Grade P Class 25							Urexpan NR-201	PSI-951		1CSL		Sonolastic SL1	Vulkem 300 SSL Vulkem 45
<b>ACRYLIC LATEX</b> <b>Federal Specification</b> ASTM C 834-76	<b>321 (Siliconized)</b> <b>800 (Siliconized)</b> <b>CRL15W</b>			Alex-Plus Alex Painters Caulk Kwik Seal	SA-167 LC-160		AC-20	PSI-701	8500			Sonolac	Tremco 834
<b>ACRYLIC SEALANT</b> <b>Federal Specification</b> TT-S-00230	<b>U60 (Uni-crylic Polymer)</b>						60+ Unicrylic Acrylic (Terpolymer)						Mono555 (Acrylic Terpolymer)
<b>BUTYL RUBBER</b> <b>Federal Specification</b> TT-C-00598, TT-S-001657, TT-C-1796A ASTM C1085 & C1311	<b>777</b> <b>888</b>	B-100 AP-77		Butyl-Flex	SBR-100	757	BC-158	PSI-301					Butyl Sealant
<b>ACOUSTICAL / CURTAINWALL</b> AAMA 809.2 NAAMM SS-1A-68		BP-400			SC-170 (Solvent) SC-175 (WB)	707							Tremco Curtain-wall Sealant

Click on a Brand or Sealant Type, and if we have a match you will go to that page, if not please inquire with CRL Technical Sales for availability.

All information is deemed to be accurate and current to the best of our knowledge. If up to date information is needed please contact CRL Technical Sales by calling Toll Free (800) 421-6144 extension 777 or by e-mail.